ANALOG DEVICES

Octal 8-Bit TrimDAC with Power Shutdown

AD8801/AD8803

FEATURES
Low Cost
Replaces Eight Potentiometers
Eight Individually Programmable Outputs
Three-Wire Serial Input
Power Shutdown $\leq 25\ \mu$W Including I_{DD} and I_{REF}
Midscale Preset, AD8801
Separate V_{REFL} Range Setting, AD8803
+3 V to +5 V Single Supply Operation

APPLICATIONS
Automatic Adjustment
Trimmer Potentiometer Replacement
Video and Audio Equipment Gain and Offset Adjustment
Portable and Battery Operated Equipment

GENERAL DESCRIPTION
The AD8801/AD8803 provides eight digitally controlled dc voltage outputs. This potentiometer divider TrimDAC® allows replacement of the mechanical trimmer function in new designs. The AD8801/AD8803 is ideal for dc voltage adjustment applications.

Easily programmed by serial interfaced microcontroller ports, the AD8801 with its midscale preset is ideal for potentiometer replacement where adjustments start at a nominal value. Applications such as gain control of video amplifiers, voltage controlled frequencies and bandwidths in video equipment, geometric correction and automatic adjustment in CRT computer graphic displays are a few of the many applications ideally suited for these parts. The AD8803 provides independent control of both the top and bottom end of the potentiometer divider allowing a separate zero-scale voltage setting determined by the V_{REFL} pin. This is helpful for maximizing the resolution of devices with a limited allowable voltage control range.

FUNCTIONAL BLOCK DIAGRAM
(DACs 2–7 Omitted for Clarity)

Internally the AD8801/AD8803 contain eight voltage output digital-to-analog converters, sharing a common reference voltage input.

Each DAC has its own DAC register that holds its output state. These DAC registers are updated from an internal serial-to-parallel shift register that is loaded from a standard three-wire serial input digital interface. Eleven data bits make up the data word clocked into the serial input register. This data word is decoded where the first 3 bits determine the address of the DAC register to be loaded with the last 8 bits of data. The AD8801/AD8803 consumes only 5 μA from 5 V power supplies. In addition, in shutdown mode reference input current consumption is also reduced to 5 μA while saving the DAC latch settings for use after return to normal operation.

The AD8801/AD8803 is available in 16-pin plastic DIP and the 1.5 mm height SO-16 surface mount packages.

See the AD8802/AD8804 for a twelve channel version of this product.

TrimDAC is a registered trademark of Analog Devices, Inc.

REV. A

AD8801/AD8803– SPECIFICATIONS

(V_{DD} = +3 V ± 10% or +5 V ± 10%, V_{REFH} = +V_{DD}, V_{REFL} = 0 V, –40°C ≤ T_A ≤ +85°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ[1]	Max	Units
STATIC ACCURACY						
Specifications Apply to All DACs						
Resolution	N		8			Bits
Integral Nonlinearity Error	INL		–1.5	±1/2	+1.5	LSB
Differential Nonlinearity	DNL	Guaranteed Monotonic	–1	±1/4	+1	LSB
Full-Scale Error	G_{FSE}		–4	–2.8	+0.5	LSB
Zero-Code Error	V_{ZSE}		–0.5	±0.1	+0.5	LSB
DAC Output Resistance	R_{OUT}		3	5	8	kΩ
Output Resistance Match	$\Delta R/R_O$			1		%
REFERENCE INPUT						
Voltage Range[2]	V_{REFH}		0		V_{DD}	V
	V_{REFL}	Pin Available on AD8803 Only	0		V_{DD}	V
Input Resistance	R_{REFH}	Digital Inputs = 55$_H$, V_{REFH} = V_{DD}		2		kΩ
Reference Input Capacitance[3]	C_{REF0}	Digital Inputs All Zeros		25		pF
	C_{REF1}	Digital Inputs All Ones		25		pF
DIGITAL INPUTS						
Logic High	V_{IH}	V_{DD} = +5 V	2.4			V
Logic Low	V_{IL}	V_{DD} = +5 V			0.8	V
Logic High	V_{IH}	V_{DD} = +3 V	2.1			V
Logic Low	V_{IL}	V_{DD} = +3 V			0.6	V
Input Current	I_{IL}	V_{IN} = 0 V or +5 V			±1	µA
Input Capacitance[3]	C_{IL}			5		pF
POWER SUPPLIES[4]						
Power Supply Range	V_{DD} Range		2.7		5.5	V
Supply Current (CMOS)	I_{DD}	V_{IH} = V_{DD} or V_{IL} = 0 V		0.01	5	µA
Supply Current (TTL)	I_{DD}	V_{IH} = 2.4 V or V_{IL} = 0.8 V, V_{DD} = +5.5 V		1	4	mA
Shutdown Current	I_{REFH}	$\overline{SHDN}$ = 0		0.01	5	µA
Power Dissipation	P_{DISS}	V_{IH} = V_{DD} or V_{IL} = 0 V, V_{DD} = +5.5 V			27.5	µW
Power Supply Sensitivity	PSRR	V_{DD} = 5 V ± 10%, V_{REFH} = +4.5 V		0.001	0.002	%/%
Power Supply Sensitivity	PSRR	V_{DD} = 3 V ± 10%, V_{REFH} = +2.7 V		0.01		%/%
DYNAMIC PERFORMANCE[3]						
V_{OUT} Settling Time (Positive or Negative)	t_S	±1/2 LSB Error Band		0.6		µs
Crosstalk	CT	See Note 5, f = 100 kHz		50		dB
SWITCHING CHARACTERISTICS[3, 6]						
Input Clock Pulse Width	t_{CH}, t_{CL}	Clock Level High or Low	15			ns
Data Setup Time	t_{DS}		5			ns
Data Hold Time	t_{DH}		5			ns
$\overline{CS}$ Setup Time	t_{CSS}		10			ns
$\overline{CS}$ High Pulse Width	t_{CSW}		10			ns
Reset Pulse Width	t_{RS}		60			ns
CLK Rise to $\overline{CS}$ Rise Hold Time	t_{CSH}		15			ns
$\overline{CS}$ Rise to Next Rising Clock	t_{CS1}		10			ns

NOTES

[1]Typical values represent average readings measured at +25°C.

[2]V_{REFH} can be any value between GND and V_{DD}, for the AD8803 V_{REFL} can be any value between GND and V_{DD}.

[3]Guaranteed by design and not subject to production test.

[4]Digital Input voltages V_{IN} = 0 V or V_{DD} for CMOS condition. DAC outputs unloaded. P_{DISS} is calculated from ($I_{DD} \times V_{DD}$).

[5]Measured at a V_{OUT} pin where an adjacent V_{OUT} pin is making a full-scale voltage change.

[6]See timing diagram for location of measured values. All input control voltages are specified with t_R = t_F = 2 ns (10% to 90% of V_{DD}) and timed from a voltage level of 1.6 V.

Specifications subject to change without notice.

REV. A

ABSOLUTE MAXIMUM RATINGS

(T_A = +25°C, unless otherwise noted)

V_{DD} to GND .... –0.3, +8 V
V_{REFX} to GND .... 0 V, V_{DD}
Outputs (Ox) to GND .... 0 V, V_{DD}
Digital Input Voltage to GND .... 0 V, V_{DD}
Operating Temperature Range .... –40°C to +85°C
Maximum Junction Temperature (T_J MAX) .... +150°C
Storage Temperature .... –65°C to +150°C
Lead Temperature (Soldering, 10 sec) .... +300°C
Package Power Dissipation .... (T_J MAX – T_A)/θ_{JA}
Thermal Resistance θ_{JA},
 SOIC (SO-16) .... 60°C/W
 P-DIP (N-16) .... 57°C/W

AD8801 PIN DESCRIPTIONS

| Pin	Name	Description
1	V_{REFH}	Common DAC Reference Input
2	O1	DAC Output #1, Addr = 000_2
3	O2	DAC Output #2, Addr = 001_2
4	O3	DAC Output #3, Addr = 010_2
5	O4	DAC Output #4, Addr = 011_2
6	$\overline{SHDN}$	Reference input open circuit, active low, all DAC outputs open circuit. DAC latch settings maintained.
7	$\overline{CS}$	Chip Select Input, active low. When $\overline{CS}$ returns high, data in the serial input register is decoded based on the address bits and loaded into the target DAC register.
8	GND	Ground
9	CLK	Serial Clock Input, Positive Edge Triggered
10	SDI	Serial Data Input
11	O5	DAC Output #5, Addr = 100_2
12	O6	DAC Output #6, Addr = 101_2
13	O7	DAC Output #7, Addr = 110_2
14	O8	DAC Output #8, Addr = 111_2
15	$\overline{RS}$	Asynchronous preset to midscale output setting, active low. Loads all DAC latches with 80_H.
16	V_{DD}	Positive power supply, specified for operation at both +3 V and +5 V.

ORDERING GUIDE

Model	FTN	Temperature	Package Description	Package Option
AD8801AN	$\overline{RS}$	–40°C to +85°C	PDIP-16	N-16
AD8801AR	$\overline{RS}$	–40°C to +85°C	SO-16	R-16A
AD8803AN	REFL	–40°C to +85°C	PDIP-16	N-16
AD8803AR	REFL	–40°C to +85°C	SO-16	R-16A

AD8803 PIN DESCRIPTIONS

Pin	Name	Description
1	V_{REFH}	Common High-Side DAC Reference Input
2	O1	DAC Output #1, Addr = 000_2
3	O2	DAC Output #2, Addr = 001_2
4	O3	DAC Output #3, Addr = 010_2
5	O4	DAC Output #4, Addr = 011_2
6	$\overline{SHDN}$	Reference inputs open circuit, active low, all DAC outputs open circuit. DAC latch settings maintained.
7	$\overline{CS}$	Chip Select Input, active low. When $\overline{CS}$ returns high, data in the serial input register is decoded based on the address bits and loaded into the target DAC register.
8	GND	Ground
9	V_{REFL}	Common Low-Side DAC Reference Input
10	CLK	Serial Clock Input, Positive Edge Triggered
11	SDI	Serial Data Input
12	O5	DAC Output #5, Addr = 100_2
13	O6	DAC Output #6, Addr = 101_2
14	O7	DAC Output #7, Addr = 110_2
15	O8	DAC Output #8, Addr = 111_2
16	V_{DD}	Positive power supply, specified for operation at both +3 V and +5 V.

PIN CONFIGURATIONS

AD8801 TOP VIEW (Not to Scale)

Pin	Left		Right	Pin
1	V_{REFH}		V_{DD}	16
2	O1		$\overline{RS}$	15
3	O2		O8	14
4	O3		O7	13
5	O4		O6	12
6	$\overline{SHDN}$		O5	11
7	$\overline{CS}$		SDI	10
8	GND		CLK	9

AD8803 TOP VIEW (Not to Scale)

Pin	Left		Right	Pin
1	V_{REFH}		V_{DD}	16
2	O1		O8	15
3	O2		O7	14
4	O3		O6	13
5	O4		O5	12
6	$\overline{SHDN}$		SDI	11
7	$\overline{CS}$		CLK	10
8	GND		V_{REFL}	9

AD8801/AD8803

OCTAL 8-BIT TRIMDAC, WITH SHUTDOWN

Figure 2a. Timing Diagram

DETAIL SERIAL DATA INPUT TIMING ($\overline{RS}$ = "1")

*Figure 2b. Detail Timing Diagram*

RESET TIMING

Figure 2c. Reset Timing Diagram

Table I. Serial-Data Word Format

ADDR			DATA							
B10	B9	B8	B7	B6	B5	B4	B3	B2	B1	B0
A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0
MSB		LSB	MSB							LSB
2^{10}	2^9	2^8	2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0

OPERATION

The AD8801/AD8803 provides eight channels of programmable voltage output adjustment capability. Changing the programmed output voltage of each TrimDAC is accomplished by clocking in an 11-bit serial data word into the SDI (Serial Data Input) pin. The format of this data word is three address bits, MSB first, followed by eight data bits, MSB first. Table I provides the serial register data word format. The AD8801/AD8803 has the

following address assignments for the ADDR decode which determines the location of DAC register receiving the serial register data in bits B7 through B0:

$$DAC \# = A2 \times 4 + A1 \times 2 + A0 + 1$$

DAC outputs can be changed one at a time in random sequence. The fast serial-data loading of 33 MHz makes it possible to load all eight DACs in as little time as 3 μs (12 × 8 × 30 ns). The exact timing requirements are shown in Figure 2.

The AD8801 offers a midscale preset activated by the $\overline{RS}$ pin simplifying initial setting conditions at first power up. The AD8803 has both a V_{REFH} and a V_{REFL} pin to establish independent positive full-scale and zero-scale settings to optimize resolution. Both parts offer a power shutdown $\overline{SHDN}$ that places the DAC structure in a zero power consumption state resulting in only leakage currents being consumed from the power supply, V_{REF} inputs, and all 8 outputs. In shutdown mode the DACx latch settings are maintained. When returning to operational mode from power shutdown the DAC outputs return to their previous voltage settings.


Figure 3. AD8801/AD8803 Equivalent TrimDAC Circuit

PROGRAMMING THE OUTPUT VOLTAGE

The output voltage range is determined by the external reference connected to V_{REFH} and V_{REFL} pins. See Figure 3 for a simplified diagram of the equivalent DAC circuit. In the case of the AD8801, its V_{REFL} is internally connected to GND and therefore cannot be offset. V_{REFH} can be tied to V_{DD} and V_{REFL} can be tied to GND establishing a basic rail-to-rail voltage output programming range. Other output ranges are established by the use of different external voltage references. The general transfer equation that determines the programmed output voltage is:

$$V_O(Dx) = (Dx)/256 \times (V_{REFH} - V_{REFL}) + V_{REFL} \qquad (1)$$

where Dx is the data contained in the 8-bit DACx latch.

For example, when V_{REFH} = +5 V and V_{REFL} = 0 V the following output voltages will be generated for the following codes:

D	V_{OX}	Output State (V_{REFH} = +5 V, V_{REFL} = 0 V)
255	4.98 V	Full-Scale
128	2.50 V	Half-Scale (Midscale Reset Value)
1	0.02 V	1 LSB
0	0.00 V	Zero-Scale

REFERENCE INPUTS (V_{REFH}, V_{REFL})

The reference input pins set the output voltage range of all eight DACs. In the case of the AD8801 only the V_{REFH} pin is available to establish a user designed full-scale output voltage. The external reference voltage can be any value between 0 and V_{DD} but must not exceed the V_{DD} supply voltage. In the case of the AD8803, which has access to the V_{REFL} which establishes the zero-scale output voltage, any voltage can be applied between 0 V and V_{DD}. V_{REFL} can be smaller or larger in voltage than V_{REFH} since the DAC design uses fully bidirectional switches as shown in Figure 3. The input resistance to the DAC has a code dependent variation that has a nominal worst case measured at 55_H, which is approximately 2 kΩ. When V_{REFH} is greater than V_{REFL}, the REFL reference must be able to sink current out of the DAC ladder, while the REFH reference is sourcing current into the DAC ladder. The DAC design minimizes reference glitch current maintaining minimum interference between DAC channels during code changes.

DAC OUTPUTS (O1–O8)

The eight DAC outputs present a constant output resistance of approximately 5 kΩ independent of code setting. The distribution of R_{OUT} from DAC to DAC typically matches within ±1%. However, device to device matching is process lot dependent having a ±20% variation. The change in R_{OUT} with temperature has a 500 ppm/°C temperature coefficient. During power shutdown all eight outputs are open circuited.


Figure 4. Block Diagram

DIGITAL INTERFACING

The AD8801/AD8803 contains a standard three-wire serial input control interface. The three inputs are clock (CLK), $\overline{CS}$ and serial data input (SDI). The positive-edge sensitive CLK input requires clean transitions to avoid clocking incorrect data into the serial input register. Standard logic families work well. If mechanical switches are used for product evaluation, they should be debounced by a flip-flop or other suitable means. Figure 4 block diagram shows more detail of the internal digital circuitry. When $\overline{CS}$ is taken active low, the clock can load data into the serial register on each positive clock edge, see Table II.

Table II. Input Logic Control Truth Table

$\overline{CS}$	CLK	Register Activity
1	X	No effect.
0	P	Shifts Serial Register one bit loading the next bit in from the SDI pin.
P	X	Data is transferred from the serial register to the decoded DAC register. See Figure 5.

NOTE: P = positive edge, X = don't care.

The data setup and data hold times in the specification table determine the data valid time requirements. The last 11 bits of the data word entered into the serial register are held when $\overline{CS}$ returns high. At the same time $\overline{CS}$ goes high it gates the address decoder which enables one of the eight positive edge triggered DAC registers, see Figure 5 detail.


Figure 5. Equivalent Control Logic

The target DAC register is loaded with the last eight bits of the serial data word completing one DAC update. Eight separate 11-bit data words must be clocked in to change all eight output settings.

All digital inputs are protected with a series input resistor and parallel Zener ESD structure shown in Figure 6. This applies to digital input pins $\overline{CS}$, SDI, $\overline{RS}$, $\overline{SHDN}$, CLK.


Figure 6. Equivalent ESD Protection Circuit

Digital inputs can be driven by voltages exceeding the AD8801/AD8803 V_{DD} value. This allows 5 V logic to interface directly to the part when it is operated at 3 V.

# AD8801/AD8803– Typical Performance Characteristics


Figure 7. INL vs. Code


Figure 10. Input Reference Current vs. Code

Figure 8. Differential Nonlinearity Error vs. Code

Figure 11. Shutdown Current vs. Temperature


Figure 9. Total Unadjusted Error Histogram

Figure 12. Supply Current vs. Temperature

REV. A

Figure 13. Supply Current vs. Logic Input Voltage

Figure 16. Adjacent Channel Clock Feedthrough


Figure 14. Power Supply Rejection vs. Frequency

Figure 17. Midscale Transition


Figure 15. Large-Signal Settling Time

Figure 18. Zero-Scale Error Accelerated by Burn-In

Figure 19. Full-Scale Error Accelerated by Burn-In


Figure 20. REF Input Resistance Accelerated by Burn-In

APPLICATIONS

Supply Bypassing

Precision analog products, such as the AD8801/AD8803, require a well filtered power source. Since the AD8801/AD8803 operate from a single +3 V to +5 V supply, it seems convenient to simply tap into the digital logic power supply. Unfortunately, the logic supply is often a switch-mode design, which generates noise in the 20 kHz to 1 MHz range. In addition, fast logic gates can generate glitches hundred of millivolts in amplitude due to wiring resistances and inductances.

If possible, the AD8801/AD8803 should be powered directly from the system power supply. This arrangement, shown in Figure 21, will isolate the analog section from the logic switching transients. Even if a separate power supply trace is not available, however, generous supply bypassing will reduce supply-line induced errors. Local supply bypassing consisting of a 10 μF tantalum electrolytic in parallel with a 0.1 μF ceramic capacitor is recommended (Figure 22).

Figure 21. Use Separate Traces to Reduce Power Supply Noise

Figure 22. Recommended Supply Bypassing for the AD8801/AD8803

Buffering the AD8801/AD8803 Output

In many cases, the nominal 5 kΩ output impedance of the AD8801/AD8803 is sufficient to drive succeeding circuitry. If a lower output impedance is required, an external amplifier can be added. Several examples are shown in Figure 23. One amplifier of an OP291 is used as a simple buffer to reduce the output resistance of DAC A. The OP291 was chosen primarily for its rail-to-rail input and output operation, but it also offers operation to less than 3 V, low offset voltage, and low supply current.

The next two DACs, B and C, are configured in a summing arrangement where DAC C provides the coarse output voltage setting and DAC B can be used for fine adjustment. The insertion of R1 in series with DAC B attenuates its contribution to the voltage sum node at the DAC C output.

REV. A

Figure 23. Buffering the AD8801/AD8803 Output

Increasing Output Voltage Swing

An external amplifier can also be used to extend the output voltage swing beyond the power supply rails of the AD8801/AD8803. This technique permits an easy digital interface for the DAC, while expanding the output swing to take advantage of higher voltage external power supplies. For example, DAC A of Figure 24 is configured to swing from –5 V to +5 V. The actual output voltage is given by:

$$V_{OUT} = \left(1 + \frac{R_F}{R_S}\right) \times \left(\frac{D}{256} \times 5V\right) - 5V$$

Where D is the DAC input value (i.e., 0 to 255). This circuit can be combined with the "fine/coarse" circuit of Figure 23 if, for example, a very accurate adjustment around 0 V is desired.

Figure 24. Increasing Output Voltage Swing

DAC B of Figure 24 is in a noninverting gain of two configuration, which increases the available output swing to +10 V. The feedback resistors can be adjusted to provide any scaling of the output voltage, within the limits of the external op amp power supplies.

Microcomputer Interfaces

The AD8801/AD8803 serial data input provides an easy interface to a variety of single-chip microcomputers (μCs). Many μCs have a built-in serial data capability that can be used for communicating with the DAC. In cases where no serial port is provided, or it is being used for some other purpose (such as an RS-232 communications interface), the AD8801/AD8803 can easily be addressed in software.

Eleven data bits are required to load a value into the AD8801/AD8803 (3 bits for the DAC address and 8 bits for the DAC value). If more than 11 bits are transmitted before the Chip Select input goes high, the extra (i.e., the most-significant) bits are ignored. This feature is valuable because most μCs only transmit data in 8-bit increments. Thus, the μC will send 16 bits to the DAC instead of 11 bits. The AD8801/AD8803 will only respond to the last 11 bits clocked into the SDI input, however, so the serial data interface is not affected.

An 8051 μC Interface

A typical interface between the AD8801/AD8803 and an 8051 μC is shown in Figure 25. This interface uses the 8051's internal serial port. The serial port is programmed for Mode 0 operation, which functions as a simple 8-bit shift register. The 8051's Port3.0 pin functions as the serial data output, while Port3.1 serves as the serial clock.

Figure 25. Interfacing the 8051 μC to an AD8801/AD8803, Using the Serial Port

When data is written to the Serial Buffer Register (SBUF, at Special Function Register location 99$_H$), the data is automatically converted to serial format and clocked out via Port3.0 and Port3.1. After 8 bits have been transmitted, the Transmit Interrupt flag (SCON.1) is set and the next 8 bits can be transmitted.

The AD8801 and AD8803 require the Chip Select to go low at the beginning of the serial data transfer. In addition, the SCLK input must be high when the Chip Select input goes high at the end of the transfer. The 8051's serial clock meets this requirement, since Port3.1 both begins and ends the serial data in the high state.

Software for the 8051 Interface

A software routine for the AD8801/AD8803 to 8051 interface is shown in Listing 1. The routine transfers the 8-bit data stored at data memory location DAC_VALUE to the AD8801/AD8803 DAC addressed by the contents of location DAC_ADDR.

AD8801/AD8803

```
;
;  This subroutine loads an AD8801/AD8803 DAC from an 8051 microcomputer,
;  using the 8051's serial port in MODE 0 (Shift Register Mode).
;  The DAC value is stored at location DAC_VAL
;  The DAC address is stored at location DAC_ADDR
;
;  Variable declarations
;
PORT1           DATA        90H                         ;SFR register for port 1
DAC_VALUE       DATA        40H                         ;DAC Value
DAC_ADDR        DATA        41H                         ;DAC Address
SHIFT1          DATA        042H                        ;high byte of 16-bit answer
SHIFT2          DATA        043H                        ;low byte of answer
SHIFT_COUNT     DATA        44H                         ;
;
                ORG         100H                        ;arbitrary start
DO_8801:        CLR         SCON.7                      ;set serial
                CLR         SCON.6                      ;  data mode 0
                CLR         SCON.5
                CLR         SCON.1                      ;clr transmit flag
                ORL         PORT1.1,#00001110B          ;/RS, /SHDN, /CS high
                CLR         PORT1.1                     ;set the /CS low
                MOV         SHIFT1,DAC_ADDR             ;put DAC value in shift register
                ACALL       BYTESWAP                    ;
                MOV         SBUF,SHIFT2                 ;send the address byte
ADDR_WAIT:      JNB         SCON.1,ADDR_WAIT            ;wait until 8 bits are sent
                CLR         SCON.1                      ;clear the serial transmit flag
                MOV         SHIFT1,DAC_VALUE            ;send the DAC value
                ACALL       BYTESWAP                    ;
                MOV         SBUF,SHIFT2                 ;
VALU_WAIT:      JNB         SCON.1,VALU_WAIT            ;wait again
                CLR         SCON.1                      ;clear serial flag
                SETB        PORT1.1                     ;/CS high, latch data
                RET                                     ; into AD8801
;
BYTESWAP:       MOV         SHIFT_COUNT,#8              ;Shift 8 bits
SWAP_LOOP:      MOV         A,SHIFT1                    ;Get source byte
                RLC         A                          ;Rotate MSB to carry
                MOV         SHIFT1,A                    ;Save new source byte
                MOV         A,SHIFT2                    ;Get destination byte
                RRC         A                          ;Move carry to MSB
                MOV         SHIFT2,A                    ;Save
                DJNZ        SHIFT_COUNT,SWAP_LOOP       ;Done?
                RET
                END
```

Listing 1. Software for the 8051 to AD8801/AD8803 Serial Port Interface

The subroutine begins by setting appropriate bits in the Serial Control register to configure the serial port for Mode 0 operation. Next the DAC's Chip Select input is set low to enable the AD8801/AD8803. The DAC address is obtained from memory location DAC_ADDR, adjusted to compensate for the 8051's serial data format, and moved to the serial buffer register. At this point, serial data transmission begins automatically. When all 8 bits have been sent, the Transmit Interrupt bit is set, and the subroutine then proceeds to send the DAC value stored at location DAC_VALUE. Finally the Chip Select input is returned high, causing the appropriate AD8801/AD8803 output voltage to change, and the subroutine ends.

The 8051 sends data out of its shift register LSB first, while the AD8801/AD8803 require data MSB first. The subroutine therefore includes a BYTESWAP subroutine to reformat the data. This routine transfers the MSB-first byte at location SHIFT1 to an LSB-first byte at location SHIFT2. The routine rotates the MSB of the first byte into the carry with a Rotate Left Carry instruction, then rotates the carry into the MSB of the second byte with a Rotate Right Carry instruction. After 8 loops, SHIFT2 contains the data in the proper format.

The BYTESWAP routine in Listing 1 is convenient because the DAC data can be calculated in normal LSB form. For example, producing a ramp voltage on a DAC is simply a matter of repeatedly incrementing the DAC_VALUE location and calling the LD_8801 subroutine.

If the μC's hardware serial port is being used for other purposes, the AD8801/AD8803 can be loaded by using the parallel port. A typical parallel interface is shown in Figure 26. The serial data is transmitted to the DAC via the 8051's Port1.7 output, while Port1.6 acts as the serial clock.

Software for the interface of Figure 26 is contained in Listing 2. The subroutine will send the value stored at location DAC_VALUE to the AD8801/AD8803 DAC addressed by location DAC_ADDR. The program begins by setting the AD8801/AD8803's Serial Clock and Chip Select inputs high, then setting Chip Select low to start the serial interface process. The DAC address is loaded into the accumulator and three Rotate Right shifts are performed. This places the DAC address in the 3 MSBs of the accumulator. The address is then sent to the AD8801/AD8803 via the SEND_SERIAL subroutine. Next, the DAC value is loaded into the accumulator and sent to the AD8801/AD8803. Finally, the Chip Select input is set high to complete the data transfer.

```
;  This 8051 µC subroutine loads an AD8801 or AD8803 DAC with an 8-bit value,
;  using the 8051's parallel port #1.
;  The DAC value is stored at location DAC_VALUE
;  The DAC address is stored at location DAC_ADDR
;
;  Variable declarations
PORT1            DATA        90H                                    ;SFR register for port 1
DAC_VALUE        DATA        40H                                    ;DAC Value
DAC_ADDR         DATA        41H                                    ;DAC Address (0 through 7)
LOOPCOUNT        DATA        43H                                    ;COUNT LOOPS
                 ;
                 ORG         100H                                   ;arbitrary start
LD_8803:         ORL         PORT1,#11110000B                       ;set CLK, /CS and /SHDN high,
                 CLR         PORT1.5                                ;Set Chip Select low
                 MOV         LOOPCOUNT,#3                           ;Address is 3 bits
                 MOV         A,DAC_ADDR                             ; Get DAC address
                 RR          A                                      ;  Rotate the DAC
                 RR          A                                      ;address to the Most
                 RR          A                                      ;Significant Bits (MSBs)
                 ACALL       SEND_SERIAL                            ;Send the address
                 MOV         LOOPCOUNT,#8                           ;Do 8 bits of data
                 MOV         A,DAC_VALUE
                 ACALL       SEND_SERIAL                            ;Send the data
                 SETB        PORT1.5                                ;Set /CS high
                 RET                                                ;DONE

SEND_SERIAL:     RLC         A                                      ;Move next bit to carry
                 MOV         PORT1.7,C                              ;Move data to SDI
                 CLR         PORT1.6                                ;Pulse the
                 SETB        PORT1.6                                ;  CLK input
                 DJNZ        LOOPCOUNT,SEND_SERIAL                  ;Loop if not done
                 RET;
                 END
```

*Listing 2. Software for the 8051 to AD8801/AD8803 Parallel Port Interface*

Figure 26. An AD8801/AD8803-8051 μC Interface Using Parallel Port 1

Unlike the serial port interface of Figure 25, the parallel port interface only transmits 11 bits to the AD8801/AD8803. Also, the BYTESWAP subroutine is not required for the parallel interface, because data can be shifted out MSB first. However, the results of the two interface methods are exactly identical. In most cases, the decision on which method to use will be determined by whether or not the serial data port is available for communication with the AD8801/AD8803.

An MC68HC11-to-AD8801/AD8803 Interface

Like the 8051, the MC68HC11 includes a dedicated serial data port (labeled SPI). The SPI port provides an easy interface to the AD8801/AD8803 (Figure 27). The interface uses three lines of Port D for the serial data, and one or two lines from Port C to control the $\overline{SHDN}$ and $\overline{RS}$ (AD8801 only) inputs.

*ADDITIONAL PINS OMITTED FOR CLARITY

Figure 27. An AD8801/AD8803-to-MC68HC11 Interface

A software routine for loading the AD8801/AD8803 from a 68HC11 evaluation board is shown in Listing 3. First, the MC68HC11 is configured for SPI operation. Bits CPHA and CPOL define the SPI mode wherein the serial clock (SCK) is high at the beginning and end of transmission, and data is valid on the rising edge of SCK. This mode matches the requirements of the AD8801/AD8803. After the registers are saved on the stack, the DAC value and address are transferred to RAM and the AD8801/AD8803's $\overline{CS}$ is driven low. Next, the DAC's address byte is transferred to the SPDR register, which automatically initiates the SPI data transfer. The program tests the SPIF bit and loops until the data transfer is complete. Then the DAC value is sent to the SPI. When transmission of the second byte is complete, $\overline{CS}$ is driven high to load the new data and address into the AD8801/AD8803.

```
*
* AD8801/AD8803 to M68HC11 Interface Assembly Program
*
* M68HC11 Register definitions
*
PORTC          EQU          $1003          Port C control register
*                                          "0,0,0,0;0,0,RS/, SHDN/"
DDRC           EQU          $1007          Port C data direction
PORTD          EQU          $1008          Port D data register
*                                          "0,0,/CS,CLK;SDI,0,0,0"
DDRD           EQU          $1009          Port D data direction
SPCR           EQU          $1028          SPI control register
*                                          "SPIE,SPE,DWOM,MSTR;CPOL,CPHA,SPR1,SPR0"
SPSR           EQU          $1029          SPI status register
*                                          "SPIF,WCOL,0,MODF;0,0,0,0"
SPDR           EQU          $102A          SPI data register; Read-Buffer; Write-Shifter
*
* SDI RAM variables:                       SDI1 is encoded from 0 (Hex) to 7 (Hex)
*                                          SDI2 is encoded from 00 (Hex) to FF (Hex)
*                                          AD8801/3 requires two 8-bit loads; upper 5 bits
*                                          of SDI1 are ignored. AD8801/3 address bits in last
*                                          three LSBs of SDI1.
*
SDI1           EQU          $00            SDI packed byte 1 "0,0,0,0;0,A2,A1,A0"
SDI2           EQU          $01            SDI packed byte 2 "DB7,DB6,DB5,DB4;DB3,DB2,DB1,DB0"
*
* Main Program
*
               ORG          $C000          Start of user's RAM in EVB
INIT           LDS          #$CFFF         Top of C page RAM
*
* Initialize Port C Outputs
*
               LDAA         #$03           0,0,0,0;0,0,1,1
*                                          /RS-Hi, /SHDN-Hi
               STAA         PORTC          Initialize Port C Outputs
               LDAA         #$03           0,0,0,0;0,0,1,1
               STAA         DDRC           /RS and /SHDN are now enabled as outputs
*
* Initialize Port D Outputs
*
               LDAA         #$20           0,0,1,0;0,0,0,0
*                                          /CS-Hi,/CLK-Lo,SDI-Lo
               STAA         PORTD          Initialize Port D Outputs
               LDAA         #$38           0,0,1,1;1,0,0,0
               STAA         DDRD           /CS,CLK, and SDI are now enabled as outputs
*
* Initialize SPI Interface
*
               LDAA         #$53
               STAA         SPCR           SPI is Master,CPHA=0,CPOL=0,Clk rate=E/32
*
* Call update subroutine
*
               BSR          UPDATE         Xfer 2 8-bit words to AD8402
               JMP          $E000          Restart BUFFALO
*
* Subroutine UPDATE
*
UPDATE         PSHX         Save registers X, Y, and A
```

AD8801/AD8803

```
                PSHY
                PSHA
*
* Enter Contents of SDI1 Data Register
*
                LDAA        $0000           Hi-byte data loaded from memory
                STAA        SDI1            SDI1 = data in location 0000H
*
* Enter Contents of SDI2 Data Register
*
                LDAA        $0001           Low-byte data loaded from memory
                STAA        SDI2            SDI2 = Data in location 0001H
*
                LDX         #SDI1           Stack pointer at 1st byte to send via SDI
                LDY         #$1000          Stack pointer at on-chip registers
*
* Reset AD8801 to one-half scale (AD8803 does not have a Reset input)
*
                BCLR        PORTC,Y $02     Assert /RS
                BSET        PORTC,Y $02     De-assert /RS
*
* Get AD8801/03 ready for data input
*
                BCLR        PORTD,Y $20     Assert /CS
*
TFRLP           LDAA        0,X             Get a byte to transfer via SPI
                STAA        SPDR            Write SDI data reg to start xfer
*
WAIT            LDAA        SPSR            Loop to wait for SPIF
                BPL         WAIT            SPIF is the MSB of SPSR
*                                           (when SPIF is set, SPSR is negated)
                INX                         Increment counter to next byte for xfer
                CPX         #SDI2+1         Are we done yet ?
                BNE         TFRLP           If not, xfer the second byte
*
* Update AD8801 output
*
                BSET        PORTD,Y $20     Latch register & update AD8801
*
                PULA                        When done, restore registers X, Y & A
                PULY
                PULX
                RTS                         ** Return to Main Program **
```

Listing 3. AD8801/AD8803 to MC68HC11 Interface Program Source Code

OUTLINE DIMENSIONS

Dimensions shown in inches and (mm).

16-Pin Plastic DIP Package (N-16)

16-Pin Narrow Body SOIC Package (R-16A)